

DIGITAL VIBRATION METER

Equinox[®]

Features :

- Specially designed for easy On Site Vibration measurement of all rotating machinery for quality control, commissioning, and predictive maintenance purposes.
- Individual high quality Accelerometer for accurate and repeatable measurements
- Bearing condition monitoring function
- LCD digital display
- Lightweight and easy to use
- Wide frequency range (10Hz. to 10kHz.) in acceleration mode
- Automatic power shut off to conserve power.
- AC output socket for headphones and recording.
- Optional headphones for use as electronic stethoscope.
- Optional software and cable for RS232C interface.



Specification :

Display	: 4 digits, 18 mm LCD	PC Interface	: RS232C interface (Cable and Software is not included)
Transducer	: Piezoelectric Accelerometer	Power Supply	: 4x1.5 AAA size (UM-4) batteries
Measuring Parameters	: Velocity, Acceleration, and Displacement	Power off	: Manual off at any time or Auto power off after 5 minutes from last key operation
Multifunctional type	: RPM and Frequency besides parameters mentioned above.	Operating Conditions	: <i>Temperature</i> : 0 to 50 °C <i>Humidity</i> : Below 90% RH
Measuring range:		Dimensions	: 124×62×30mm
Velocity	: 0.01-19.99 cm/s	Weight	: 120g (not including batteries)
Acceleration	: 0.1-200.0 m/s	Accessories Included:	
Displacement	: 0.001-2.000mm		Powerful Rare Earth Magnet..... 1 pc.
RPM(r/min)	: 60-99,990 RPM		Carrying Case..... 1 pc.
Frequency	: 1-20kHz Frequency range		Operation Manual..... 1 pc.
Accuracy	: ± 5%+2 digits Metric / Imperial conversion	Optional Accessories:	
Output	: AC output 2.0V peak full scale (load resistance: above 10k)		Headphones for use as Electronic Stethoscope Cable and software for RS232C



Valli Aqua and Process Instruments

1/231 A, Pananchalai Street, Adyalampattu,
(Near Raja Rajeshwari Engg. College)
Chennai - 600 095, Tamil Nadu.
Mobile : +91-9840752690
E-mail : enquiry@vapinstruments.in, kvgiri_59@yahoo.in
Website : www.vapinstruments.in