



SHORE HARDNESS TESTER - D

● APPLICATION :

Shore D is designed for Plastics, Formica, Epoxies and Plexiglass. It Meets Standards: DIN53505, ISO868, ISO7619, ASTM D 2240, JIS K7215. Used the exclusive Micro-Computer LSI Circuit & Crystal time base to offer high accuracy Measurement.



Model : EQ-HT-6510D

Features :

- Pocket size with Integrated Probe
- High Accuracy Measurement.
- Digital LCD display.
- Max. Hold Key.
- Indicator of maximum value.
- Zero Calibration Check.
- RS-232C Interface (Optional S/W & Cable).
- Automatic Power Off to conserve power.
- Low Battery Indicator

● SPECIFICATIONS		EQ-HT-6510D
Standards		DIN53505, ASTM D2240, ISO 7619, JIS K7215
Parameters Displayed		Hardness Result, Average Value, Max. Value
Measuring Range		10 to 90 HD
Measurement Deviation		$\leq \pm 1\% H$
Resolution		0.1 H
Operating Conditions		0°C to 40°C
Power Supply		4 × 1.5V AA Battery
Dimension		162 × 65 × 28 mm
Weight (Not Including Battery)		160 G
Standard Accessories	Main Unit	1
	Carrying Case	1
	Instruction Manual	1
Optional Accessories		Cable & Software for RS232C interface Test Block